



CRF®

SIZE	ART. NO.	EAN NO.
5	431-5	7340118355870
6	431-6	7340118322438
7	431-7	7340118322445
8	431-8	7340118322452
9	431-9	7340118322469
10	431-10	7340118322407
11	431-11	7340118322414
12	431-12	7340118322421

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 431

Cut resistant glove, nitrile, nitrile foam, palm-dipped, double-dipped, sandy finish, cut resistance level B, 13 gg, CRF® Technology, nylon, spandex, Cat. II, black, grey, withstands contact heat up to 100°C, oil and grease resistant palm, for allround work

PROPERTIES

Durable, good grip in oily environments

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 5,9

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11, 12

DIPPING Palm-dipped, double-dipped

DIPPING MATERIAL Nitrile, nitrile foam

LINING MATERIAL 13 gg, CRF® Technology, Nylon, Spandex

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

DISPLAY Bulk pack OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE, nylon, elastane

**CE** Cat. IIEN 420:2003
+ A1:2009EN 388:2016
4X43BEN 407:2004
X1XXXX

TEGERA® 431

PREVENTS RISK OF

Cut injuries, scratches, lacerations, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Assembly, building and construction, engineering, machine operating, metalwork, transport work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, metal fabrication, machinery and equipment, MRO, building and construction

TYPE OF WORK

Medium weight

2(3)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 431

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X43B



EN 407:2004
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com