


# Watson

7221A2TF1



## Flame retardant fleece lining with sleeves

The Watson is a flame-retardant fleece lining with long sleeves. This lining cannot be worn separately. It has undergone anti-pilling treatment and has a handy slit pocket connected to the inside pocket of the raincoat in which it can be zipped into. The knitted wind cuffs at the sleeve ends and the soft fleece fabric protect you against the cold.



# Flame retardant fleece lining with sleeves

**Watson - 7221A2TF1**

## European Standards:

- » EN ISO 14116 : 2008 / Index 1/12H/40
- » EN 14058 : 2004 / Class 1 x x x x
- » EN ISO 13688 : 2013

## Exterior:

- » Zip closure
- » Slitopening to inside pocket of rain jacket
- » Round inset sleeves
- » Knitted wind cuffs at end of sleeves
- » Not to be worn separately
- » Back length 72 cm (L)

## Fabric:

Double sided fleece: 100% flame retardant polyester;  $\pm 275 \text{ g/m}^2$

## Sizes:

S - XXXL

## Colour:

- » B75 Navy Blue

## I.L.S.:

7218 – 7219

## Packaging:

5 pieces per box

## Wash and care instructions:



### SIOEN head office

Fabriekstraat 23

B-8850 Ardooie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

[www.sioen-ppc.com](http://www.sioen-ppc.com)



**Discover  
our products**

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.